

Sicherheitsleuchte ILS R - Einzelbatterie



Abstandstabelle ILS R - Rundstrahloptik - Versorgungszeit 1h

Montagehöhe [m]				
2.50	4,70	10,50	10,50	4,70
3.00	5,10	11,90	11,90	5,10
3.50	5,20	13,20	13,20	5,20
4.00	5,20	14,10	14,10	5,20
4.50	5,00	14,60	14,60	5,00
5.00	4,50	14,90	14,90	4,50
5.50	3,30	14,80	14,80	3,30
6.00	2,00	14,60	14,60	2,00
6.50	0,90	14,20	14,20	0,90
7.00	0,80	12,00	12,00	0,80


Abstandstabelle ILS R - Rundstrahloptik - Versorgungszeit 3h

Montagehöhe [m]				
2.50	4,70	10,50	10,50	4,70
3.00	5,10	11,90	11,90	5,10
3.50	5,20	13,20	13,20	5,20
4.00	5,20	14,10	14,10	5,20
4.50	5,00	14,60	14,60	5,00
5.00	4,50	14,90	14,90	4,50
5.50	3,30	14,80	14,80	3,30
6.00	2,00	14,60	14,60	2,00
6.50	0,90	14,20	14,20	0,90
7.00	0,80	12,00	12,00	0,80

Sicherheitsleuchte ILS R - Einzelbatterie



Abstandstabelle ILS R - Rundstrahloptik - Versorgungszeit 8h

Montagehöhe [m]				
2.50	3,40	9,00	9,00	3,40
3.00	3,20	9,60	9,60	3,20
3.50	2,40	9,70	9,70	2,40
4.00	1,10	9,50	9,50	1,10
4.50	1,00	7,70	7,70	1,00
5.00	1,00	6,00	6,00	1,00